HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 92008590011
BRIDGE OWNER: WEAKLEY COUNTY

ROAD NAME: OLD SR22

CROSSING: MIDDLE FORK OBION RIVER
LATITUDE:: N 36.25031 DEGREES
LONGITUDE: W 88.65369 DEGREES

COUNTY: WEAKLEY
ROUTE: 00859
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 10.31

YEAR BUILT: 1938

		TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	CONCRETE - STRINGER/MULTI-BEA		NOT APPLICABLE
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN	IT ON CONCRETE SPREAD FOOTIN	NG FOUNDATION
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE COLUMNS WITH SOLID	WEB WALL (DUMB BELL) ON CON	CRETE SPREAD FOOTING FOUNDATION
		SCOUR EVALUATION -	
	unknown foundations. Risk of sco icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.
		INSPECTION PROCEDURES -	
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert	
•			I Maintenance Personnel
		[] THP or Local Law Enf	orcement Personnel
		[] Other:	
[] - Span 1. 0 2. 0 [] - Chec [] - Chec	heck on a bridge during floods movement - horizontally as we check displacement / deflection check for plumb of piers or ben k for embankment erosion k for drift build-up on piers or ben k pier exposure, if possible, an ew the latest bridge inspection	ell as vertically along curb line, both bridge ts. pents d compare to previous inspe	
If Closure is	recommended:		
Cour temp] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.		
	maintained)		
	(2) City or County Highway	Maintenance Official (if bri	idge is not State maintained)
	(3) Tennessee Highway Pa	trol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	tate District maintenance or local highway maintenance bridge on the selected detour route shall be checked		
	dge can be re-opened only after a TDOT bridge inspection team checks the substructure nd they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 364-5413		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 364-2284		
COUNTY SHERIFF'S OFFICE	(731) 364-5454		
The report shall include the date and time of as appropriate, photographs of the bridge an	Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:			
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report	ection:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade			
SAFFIY HAZARD KEE			

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19