HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 92SR1180009

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: SR118

CROSSING: CYPRESS CREEK

LATITUDE:: N 36.40406 DEGREES
LONGITUDE: W 88.71861 DEGREES

COUNTY: WEAKLEY
ROUTE: SR118
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 7.81

LON	NGITUDE: W 88.71861 DEGREES	YEAR BUILT: 1954	
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON C	ONCRETE PILE FOUNDATION	
BENTS:	CONCRETE PILE BENT ON PILE FO	UNDATION	
PIERS:	CONCRETE COLUMNS WITH SOLID	WEB WALL (DUMB BELL) ON TIMBER PILE FOUNDATION	
		OOGUP FIVALUATION	
5		SCOUR EVALUATION	
event. Deter		have been installed to reduce the risk of bridge failure during a flood iprap should be reported to TDOT for assessment. Rip-rap protection has	
		INSPECTION PROCEDURES	
What Initiat	ted the Call-out Inspection?	[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
2. 0 [] - Chec [] - Chec	Check for plumb of piers or ber ck for embankment erosion ck for drift build-up on piers or l ck pier exposure, if possible, an		
[] - Stay Cour	nty or City Maintenance Person	cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may	
-	roperly closed and barricaded.		
[] - Cont	` '	upervisor (if bridge is State maintained)	
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	y Maintenance Official (if bridge is not State maintained)	
	, ,	trol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	_	
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any bridge prior to signing the detour route. 	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
[] - The bridge can be re-opened only after a TDOT be units and they are determined to be structurally	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(731) 571-8883		
TENNESSEE HIGHWAY PATROL	(731) 423-6635		
- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection Latest Bridge Inspection Report Scour POA Report with the above Checklist	<u>n:</u>		
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole	a mintad with the fallowing managers.		
A 1000 Foot Roll of yellow Polyethylene Barricade Tape			

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape