## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



BRIDGE ID NUMBER: 92SR1180011

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: SR118 CROSSING: OVERFLOW

LATITUDE:: **N** 36.40769 **DEGREES** 

COUNTY: WEAKLEY ROUTE: SR118 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 8.06

LON	IGITUDE: W 88.71817 DEGREES	S Y	EAR BUILT: 1954	
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICAB	LE	
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	CONCRETE PILE FOUNDATION		
BENTS:	ONCRETE PILE BENT ON PILE FOUNDATION			
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
	our critical; bridge foundations de ing scour countermeasures.	etermined to be unstable for calculated scour co	onditions. Monitor bridge in	
		INSPECTION PROCEDURES		
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert		
		[ ] TDOT District or Local Maintenance	Personnel	
		[ ] THP or Local Law Enforcement Pers	sonnel	
		[ ] Other:		
Things to cl	heck on a bridge during flood	<u>s:</u>		
1. C 2. C	movement - horizontally as w Check displacement / deflectio Check for plumb of piers or be k for embankment erosion	n along curb line, both bridge rails and oute	er edge of bridge deck.	
[ ] - Checl	k for drift build-up on piers or	bents		
[ ] - Checl	k pier exposure, if possible, a	nd compare to previous inspection		
[ ] - Revie	w the latest bridge inspection	report versus current field conditions		
f Closure is	recommended:			
Coun temp	ty or City Maintenance Persor	cross road until bridge is secured and prop nnel. Use Barricade Tape, traffic cones and/ ists to stay off of the bridge until such time	or traffic flares as	
[ ] - Conta	act: (1) District Maintenance S	supervisor ( if bridge is State maintained )		
	(2) City or County Highwa	y Maintenance Official ( if bridge is not Sta	te maintained )	
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers	as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	Bridge should remain closed u FDOT bridge inspection team.	ntil the water recedes and a daylight visual	inspection is made	

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	tate District maintenance or local highway maintenance bridge on the selected detour route shall be checked	
<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
REGION BRIDGE ENGINEER	(731) 234-9561	
DISTRICT MAINTENANCE SUPERVISOR	(731) 571-8883	
TENNESSEE HIGHWAY PATROL	(731) 423-6635	
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:		
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report	ection:	
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole	Tong printed with the following manager.	
A 1000 Foot Roll of yellow Polyethylene Barricade SAFETY HAZARD KEF		
SAFELT BAZARU NEE	EP AVVAI	

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24