# **Concept Report Form**

The Concept Report Form develops an initial project vision, basis of design and report (e.g., the Concept Report) to transition into the subsequent design stages (Stages 1 through 4 in the Project Delivery Network [PDN]). This form summarizes all project components using information to complete the Concept Report.

			Genera	al Proj	ect Informa	tion				
Project Name	SR - 1 Bridg	e over North	n Fork (N.F.	.) Holsto	on River					
PIN	124387.00									
Route	Route	NHS (Y/N)	Fu	ınction	al Class		City		Coun	ty
Information	SR 1	Yes	Р	rinciple	Arterial	К	ingsport	Н	awkins/S	u <b>ll</b> ivan
Project Information	Begin Lo Mile	og End Mi	- Д	ADT <sup>1</sup>	Design Hour Vol. (DHV) <sup>1</sup>	Truck % <sup>1</sup>	Design Speed (MPH)	Posted Speed (MPH)	Base Year	Design Year
	41.24	0.2	24 48	8,750	4,875	3.00	60	50	2026	2046
Description & Standard Drawings Used	Standard Drawing: RD11-TS-3A									
Important Project History or Related Projects	See page 3 for information on Project History.								Project Details	
Project Purpose/Need	This project is expected to utilize federal funding.  The need to replace these bridges is due to the present condition of the existing bridges: -Built in 1962 -Sufficiency rating - Bridge ID 37SR0010037: 33.1 - August 18, 2021 -Sufficiency rating - Bridge ID 37SR0010038: 49.8 - August 18, 2021 -Existing structures do not provide appropriate multimodal access								Proje	
Major Environmental Considerations	mollusc, the watershed. fish species actual impa	ree (3) state Seven (7) of s is federally acts once pla	listed fish the state l listed. The ns are dev	and one listed me project eloped	cies by watersh e (1) state listed nollusc species a t is within Zone , a No Rise Cert n an Asbestos C	mammal vare also fed AE, a regula ification or	vithin the N erally listed atory flood CLOMR/LO	F. Holstor. and the c vay. Depe MR may b	n River ne (1) ning on e	

PIN: 124387.00

Multi-Modal Considerations	-Six (6) foot sidewalk to accommodate multimodal traffic across the bridges - Four (4) foot buffered bike lane to accommodate multimodal traffic across the bridges -Five (5) to five (5) feet six (6) inch sidewalk to accommodate multimodal traffic on either side of the bridges and under the CSX Railroad bridge -MM-TS-1 and MM-TS-2 were utilized for this project				
Major Project Risks	See page 4 for information on Major Project Risks.  This document is covered by 23 § 407 and its production pursuant to fulfilling public planning requirements does not waive the provisions of § 407.				
Camaant	Total Current Project Cost		Construction Year Estimate	>	
Concept Estimate and	\$ 58,700,000		\$ 72,000,000		
Timeline	Proposed Construction Year		Estimated Construction Duration	Preliminary Estimates	
Timeline	2027		3 Years	I A	

PIN: 124387.00

Executed for approval of this Concept Report	<u>Approvals</u>
Jemas D. Keelay	Aug 20, 2024
Project Management Division Director	Date
The following individuals to execute if a bridge conce	ept report:
Ded A Kmiazawyay	Aug 25, 2024
Structures Director	Date
Dexter Justis (Aug 23, 2024 15:50 EDT)	Aug 23, 2024
Regional Project Management Division Director	Date

<sup>&</sup>lt;sup>1</sup> Traffic numbers reflect identified design year

#### S.R. 1 - Supplemental Information

#### **Project Description:**

A field review was held on April 28th 2021.

The existing bridges consist of two structures that are separated by approximately six (6) inches. The proposed bridges will be separated by thirteen (13) feet.

- Bridge ID #37SR0010037: The proposed northbound structure is 592 feet long, composed of three (3) spans of 183 feet, 226 feet and 183 feet with steel I-beams. The proposed typical section will consist of two twelve (12) foot travel lanes, a six (6) foot inside shoulder, a twelve (12) foot outside shoulder with a four (4) foot bike path included in shoulder and a six and a half (6.5) foot sidewalk and concrete parapets with structural tubing. The structure has an out-to-out width of 50 feet six (6) inches. The roadway centerline and grade will remain the same.
  - Superstructure depth (Based on steel I-beams) = 95.0" = 78.9" (beam depth) + 10" (deck) + ((50.5' (bridge width) \* (0.02/2)) \* 12")
- Bridge ID #37SR0010038: The proposed southbound structure is 592 feet long, composed of three (3) spans of 183 feet, 226 feet and 183 feet with steel I-beams. The proposed typical section will consist of two twelve (12) foot travel lanes, a six (6) foot inside shoulder, a twelve (12) foot outside shoulder and a six and a half (6.5) foot sidewalk and concrete parapets with structural tubing. The structure has an out-to-out width of 50 feet six (6) inches. The roadway centerline and grade will remain the same.
  - Superstructure depth (Based on steel I-beams) = 95.0" = 78.9" (beam depth) + 10" (deck) + ((50.5' (bridge width) \* (0.02/2)) \* 12")

Construction for this project will be completed by phased construction. Before construction on the proposed bridges begins, widening improvements to the existing CSX railroad bridge must first be completed in order to allow for lane shifts during the construction phasing.

Phase one (1) consists of shifting all four (4) lanes of traffic to the south side of the existing structures. Demolish approximately 21.67' of the existing southbound structure and construct approximately 35.75' of the new southbound structure.

Phase two (2) consists of shifting southbound traffic to the far north side of the newly constructed southbound structure. Northbound traffic will remain on the existing northbound structure. Demolish approximately 21.84' of the existing northbound and southbound structure. Construct the remaining portion of the proposed southbound structure. Design speed for phase two (2) of traffic control is 45 miles per hour. It is recommended to lower the posted speed to 35 miles per hour during construction of this phase and phase three (3).

Phase three (3) consists of shifting all four lanes of traffic to the newly constructed southbound structure. Demolish the remaining 34.49' of the existing northbound structure and construct the entirety of the proposed northbound structure.

Phase four (4) consist of shifting traffic to the proposed alignments. The sidewalk on each portion of the bridges shall be completed.

#### Important Project History or Related Projects:


Existing northbound structure (#37SR0010037): twelve (12) span, 592 feet long, thirty-eight (38) feet eight (8) inch out-to-out, twenty-eight (28) feet curb-to-curb, concrete T-beams, 40 ton weight limit.


Existing southbound structure (#S37SR0010038): twelve (12) span, 592 feet long, thirty-nine (39) feet out-to-out, twenty-seven (27) feet ten (10) inch curb-to-curb, concrete T-beams, 40 ton weight limit.


The discharges for the drainage basin (StreamStats Version 4.5.3) for drainage area of 725.97 square miles: Q10 is 25,100 cfs, Q50 is 36,700 cfs and Q100 is 42,200 cfs.


#### Major Project Risks:


- Utilities: Distribution lines, water lines will need to be relocated
- A retaining wall will need to be constructed under each abutment of the CSX Railroad bridge
  - This will allow for the full typical section of the bridges to be carried through the roadway section.
     The addition of the retaining walls also provide the necessary space for lane shifts during construction.















SR 1 (US 11W) BRIDGE OVER NORTH FORK HOLSTON RIVER @ LM 41.40 & L.M. 0.00 HAWKINS COUNTY & SULLIVAN COUNTY

FIGURE 3 SR 1 L.M. 41.40




HAWKINS COUNTY & SULLIVAN COUNTY

L.M. 41.40




HAWKINS COUNTY & SULLIVAN COUNTY




SR 1 (US 11W)
BRIDGE OVER NORTH FORK HOLSTON RIVER @ LM 41.40 & L.M. 0.00 HAWKINS COUNTY & SULLIVAN COUNTY

L.M. 41.40





SCALE: 1" = 100'

SR 1 (US 11W) HAWKINS COUNTY & SULLIVAN COUNTY BRIDGE OVER N.F. HOLSTON @ L.M. 41.40 & L.M. 0.00 BRIDGE ID: 37SR0010037 & 37SR001038





BRIDGE ID: 37SR0010037 & 37SR001038






TRAFFIC CONTROL TYPICAL SECTION PHASES 1 & 2
SR 1 (US 11W) HAWKINS COUNTY & SULLIVAN COUNTY
BRIDGE OVER N.F. HOLSTON @ L.M. 41.40 & L.M. 0.00
BRIDGE ID: 37SR0010037 & 37SR001038





SR 1 (US 11W) HAWKINS COUNTY & SULLIVAN COUNTY BRIDGE OVER N.F. HOLSTON @ L.M. 41.40 & L.M. 0.00 BRIDGE ID: 37SR0010037 & 37SR001038



## **COST ESTIMATE SUMMARY**

		COST ESTIM	ATE SUMMARY		
Route:	SR 1				
Termini:	Bridge	over N.F. Holston		TN TDOT	
Scope of Work:		1.40 & L.M. 0.00			Department of Transportation
Project Type of Work:		Replacement			The stage of the stage of
County:		s/Sullivan			Estimate Developed By
Length:	0.40	Miles			Initial/Organization
Date:		ber 4, 2023			illitiai/Organization
Date.	Decem	1001 4, 2023			MG/Gresham Smith
Years Inflated:					MG/Gresnam Smith
DESCRIPTION		LOCAL	STATE	FEDERAL	
		0%	0%	0%	TOTAL
Construction Items					
Removal Items		\$0	\$0	\$0	\$127,000
Asphalt Paving		\$0	\$0	\$0	\$840,000
Concrete Pavement		\$0	\$0	\$0	\$0
Drainage		\$0	\$0	\$0	\$72,300
Appurtenances		\$0	\$0	\$0	\$206,000
Structures & Contingency		\$0	\$0	\$0	\$27,600,000
Fencing		\$0	\$0	\$0	\$0
Signalization & Lighting		\$0	\$0	\$0	\$0
Railroad Crossing		\$0	\$0	\$0	\$0
Earthwork		\$0	\$0	\$0	\$632,000
Clearing and Grubbing		\$0	\$0	\$0	\$80,000
Seeding & Sodding		\$0	\$0	\$0	\$20,200
Rip-Rap or Slope Protection		\$0	\$0	\$0	\$88,300
Guardrail		\$0	\$0	\$0	\$60,000
Signing		\$0	\$0	\$0	\$29,700
Pavement Markings		\$0	\$0	\$0	\$29,200
Maintenance of Traffic		\$0	\$0	\$0	\$343,000
Construction Lines and Stakes		\$0	\$0	\$0	\$529,000
	D	ESIGN-BID-BUILD & DE	SIGN-BUILD PERCENT	AGES	
Mobilization	10%	\$0	\$0	\$0	\$3,010,000
Additional Items	20%	\$0	\$0	\$0	\$6,030,000
Const. Contingency (Structures Not Included)	50%	\$0	\$0	\$0	\$5,780,000
Const. Eng. & Inspec.	15%	\$0	\$0	\$0	\$6,740,000
Construction Estimate	1070	\$0	\$0	\$0	\$52,200,000
Construction Estimate		LOCAL	STATE	FEDERAL	\$32,200,000
Right-of-Way & Utilties		0%	0%	0%	TOTAL
Right-of-Way		\$0	\$0	\$0	\$0
Utilities		\$0	\$0	\$0	-
		LOCAL	STATE	FEDERAL	
Preliminary Engineering		0%	0%	0%	TOTAL
Prelim. Eng.	10.0%	\$0	\$0	\$0	\$5,220,000
Project Cost		\$0	\$0	\$0	
			REVIEW TEAM		
Review	Process A		lative, and Economic D		2477 601111
		ROLE	•	GANIZATION	DATE COMPLETED
Primary Cos		e (Before Draft Report):		/Gresham Smith	12/4/2023
	Inde	pendent Cost Estimate:	,	ıch/TDOT	12/5/2023
		Manager Review:	Amy Rau	ıch/TDOT	12/5/2023

# **PAY ITEM SUMMARY**

ITEM	TDOT DESCRIPTION	UNIT	TOOL QUANTITIES	QUANTITIES	ADDITIONAL	ı	Jnit Price	TOTAL COST	
Pavment Removal			1					1.	
415-01.02	COLD PLANING BITUMINOUS PAVEMENT	SY	12813		12813 PAVEMENT RE	\$ MOVAL TO	9.94 TAL (ROUNDED)		- 1
					.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			· ·	
Asphalt Roads			ı					Ι.	
303-01	MINERAL AGGREGATE, TYPE A BASE, GRADING D	TON	11314		11314	\$	37.18		
307-(01, 02, 03).01	ASPHALT CONCRETE MIX (All Grades) (BPMB-HM) GRADING A	TON	567		567	\$	112.37		
307-01.(20 & 21 & 22) 307-(01 & 02 & 03).08	AGGREGATE (BPMB-HM) GRADING A-S MIX ASPHALT CONCRETE MIX (ALL GRADES) (BPMB-HM) GRADING B-M2	TON	380 849		380 849	\$	122.73 105.33		
402-01	BITUMINOUS MATERIAL FOR PRIME COAT (PC)	TON	10		10	\$	1,064.94		
402-01	AGGREGATE FOR COVER MATERIAL (PC)	TON	38		38	\$	89.00		
403-01	BITUMINOUS MATERIAL FOR TACK COAT (TC)	TON	8		8	\$	924.09		
411-01.07	ACS MIX (PG64-22) GRADING E SHOULDER	TON	378		378	\$	124.81		
411-(01 & 02 & 03).10	ACS MIX (F GO4-22) GRADING E STIOUEBER  ACS MIX(ALL GRADES) GRADING D	TON	1123		1123	\$	133.70		:
111 (01 & 02 & 03).10	THE MINUTES OF THE PROPERTY OF	1011	1120				TAL (ROUNDED)		
Concrete Roads									
				CON	CRETE RAMPS AND ROA	DWAYS TO	TAL (ROUNDED)	\$	
Drainage									
209-08.02	TEMPORARY SILT FENCE (WITH BACKING)	LF		1000	1000	\$	4.56	<u> </u>	
209-08.08	ENHANCED ROCK CHECK DAM	EACH		10	10	\$	492.59	<u> </u>	
607-05.02	24" CONCRETE PIPE CULVERT (CLASS III)	LF	2510	-2360	150	\$	172.02		
611-07.01	CLASS A CONCRETE (PIPE ENDWALLS)	CY	13		13	\$	1,888.61		
611-07.02	STEEL BAR REINFORCEMENT (PIPE ENDWALLS)	LB	1224	_	1224	\$	3.96		
611-12.02	CATCH BASINS, TYPE 12, > 4' - 8' DEPTH	EA	7	-7	0	\$	11,799.31		
740-10.03 740-11.03	GEOTEXTILE (TYPE III)(EROSION CONTROL) TEMPORARY SEDIMENT TUBE 18IN (18 IN)	SY LF		1000 1000	1000	\$	2.91 4.33		
740-11.05	TEIVIPORART SEDIIVIENT TOBE 1811 (18 IIV)	LF		1000			TAL (ROUNDED)	1	
Appurtenances			1 .						
701-01.01	CONCRETE SIDEWALK (4 ")	SF	0	9000	9000	\$	10.53	<u> </u>	
711-05.71	51IN SINGLE SLOPE CONCRETE BARRIER WALL	LF	2112	-1600	512	\$	217.47		1
				ROADWAY AN	D PAVEMENT APPURTER	NANCES TO	TAL (ROUNDED)	\$	
Earthwork & Mineral									
203-01	ROAD & DRAINAGE EXCAVATION (UNCLASSIFIED)	CY	12203		12203	\$	14.81	¢	1
203-01	BORROW EXCAVATION (GRADED SOLID ROCK)	TON	6725		6725	\$	32.33		2
203-03	BORROW EXCAVATION (UNCLASSIFIED)	CY	3813	7500	11313	\$	13.27		1
204-09.01	COFFERDAM	LS	70.0	1	1	\$	83,375.60		
					EARTHWORK & M				
onstruction Lines and Stakes		10						1 6	_
105-01	Construction Lines and Stakes	LS	1		1			\$	5
								Ş	
Structures									
N/A	Removal of Bridge	SF	45939		45939	\$	30.00	Ġ	1,3
N/A	New Bridge (Steel Girder):	SF	59200		59200	\$	350.00		20,7
IN/ C	Contingency - New Bridge (Steel Girder):	%	25.0%		25.0%	٠	25.0%		5,1
N/A					23.070		23.07	· · · ·	٠,٠
N/A 604-07.01	RETAINING WALL	SF	3185		3185	Ś	110.00	Ś	3

# **PAY ITEM SUMMARY**

Lighting & Signalization							
					LIGHTING & SIGNALI	ZATION TOTAL (ROUNDED)	\$
Guardrail	CHARDRAN AT DRIDGE FAIRS		200		200		<u> </u>
705-01.01	GUARDRAIL AT BRIDGE ENDS		200	700	200	\$ 99.88	\$ 19
705-06.01	W Beam GR (Type 2) Mash TL3 GUARDRAIL TERMINAL (TYPE-IN-LINE)		0	3	700	\$ 34.98	\$ 24
705-04.05			0	-5	3	\$ 590.37 \$ 3,457.56	\$ 10
705-06.20 705-04.09	Tangent Energy Absorbing Term Mash TL-3 EARTH PAD FOR TYPE 38 GR END TREATMENT		8	-5	3	\$ 3,457.56 \$ 1,122.29	
705-04.09	EARTH PAD FOR TIPE 38 GR END TREATMENT	EA		3		ARDRAIL TOTAL (ROUNDED)	\$
					GOF	INDIAL (NOUNDED)	· ·
Seeding and Sodding							
801-01	SEEDING (WITH MULCH)	UNIT	158		158	\$ 54.58	\$
801-01.07	TEMPORARY SEEDING (WITH MULCH)	UNIT	119		119	\$ 35.33	\$
801-02	SEEDING (WITHOUT MULCH)		119		119	\$ 42.37	
803-01	SODDING (NEW SOD)			500	500	\$ 2.45	
805-12.02	EROSION CONTROL BLANKET (TYPE II)			1000	1000	\$ 1.08	
						ODDING TOTAL (ROUNDED)	\$
						, , , , , , , , , , , , , , , , , , , ,	•
Maintenace of Traffic							
N/A	Traffic Control		1		1		\$ 29
712-02.02	INTERCONNECTED PORTABLE BARRIER RAIL	LF	106	1000	1106	\$ 46.05	\$ 5
					MAINTENANCE OF	TRAFFIC TOTAL (ROUNDED)	\$
Signs						Τ.	
Not Listed	Signs (Construction)	LS	1		1	\$ -	\$
					5	SIGNING TOTAL (ROUNDED)	\$
Pavement Markings	Painted Pavement Marking (8" Barrier Line)	LF		5280	5280	\$ 0.46	\$
716-05.02	Painted Pavement Marking (8 Barrier Line)  Painted Pavement Marking (6" Line)			3	3	\$ 1,176.29	\$
716-05.20 716-12.02	ENHANCED FLAT THERMO P.M. (6IN)		6.128	-3	3.128	\$ 7,419.17	\$ 2
710-12.02	ENHANCED FLAT THERIVIO P.IVI. (BIN)	LIVI	0.128	-5		RKINGS TOTAL (ROUNDED)	¢ Z
					PAVEIVIEINI IVIA	IRKINGS TOTAL (ROUNDED)	<b>→</b>
Fencing							
. c.i.e.i.g						FENCE TOTAL (ROUNDED)	Ś
						,	Ť
Rip-Rap							
709-05.05	Machined Rip-Rap (Class A-3)	TON	0	1500	1500	\$ 58.81	\$ 8
					RIP-RAP & SLOPE PROT	ECTION TOTAL (ROUNDED)	\$ 8
Clearing and Grubing							
201-01	Clearing and Grubbing	LS			1	\$ 80,000.00	
					CLEAR AND GR	UBBING TOTAL (ROUNDED)	\$ 8
Railroad At-Grade Crossing				_			
720-03-01	Railroad Crossing Signal System	LS		0.4400	0	DATION TOTAL (DOLLARS)	\$
				RAILRO	AD CROSSING OR SEPA	RATION TOTAL (ROUNDED)	\$
Utilties							
N/A	Overhead Distribution	LM	0.25		0.25	\$ 900,000	\$
N/A N/A	Underground Power		0.25		0.25	\$ 900,000	\$
N/A	Underground Water		0.25		0.25	\$ 840,000	\$
19/15	Onderground Water	LIVI	0.25	1		LITIES TOTAL (ROUNDED)	\$ 66
							<del></del>
Right-of-Way							
N/A	Right-of-Way	LS	1		1	\$0	\$
•				_		-WAY TOTAL (ROUNDED)	

COST ESTIMATE SUMMARY (2024)							
PIN	Project Type of Work	Preliminary Engineering:	Right-of-Way:	Utilities:	Construction:	Total Project Cost (2023):	
124387.00	L.M. 41.40 & L.M. 0.00	\$ 5,280,000	\$ -	\$ 660,000	\$ 52,800,000	\$ 58,800,000	

INFLATED COST							
No. of Years	Year	Preliminary Engineering:	Right-of-Way:	Utilities:	Construction:	Total Inflated Project Cost	
0	2024	\$ 5,280,000	\$ -	\$ 660,000	\$ 52,800,000	\$ 58,800,000	
1	2025	\$ 5,650,000	\$ -	\$ 706,000	\$ 56,500,000	\$ 62,900,000	
2	2026	\$ 6,050,000	\$ -	\$ 756,000	\$ 60,500,000	\$ 67,300,000	
3	2027	\$ 6,470,000	\$ -	\$ 809,000	\$ 64,700,000	\$ 72,000,000	
4	2028	\$ 6,920,000	\$ -	\$ 865,000	\$ 69,200,000	\$ 77,100,000	
5	2029	\$ 7,410,000	\$ -	\$ 926,000	\$ 74,100,000	\$ 82,500,000	

INFLATION INPUTS				
Inflation Rate:	7.00%			

#### Site Visit Attendee List

Date of site visit: April 28<sup>th</sup>, 2021

Name	Agency Division	Phone	Email
Amy Rauch	TDOT STID	615-741-0969	Amy.rauch@tn.gov
Shaun Armstrong	TDOT STID	615-253-5327	Shaun.armstrong@tn.gov
Konner Spradlin	TDOT STID	615-253-2432	Konner.spradlin@tn.gov
Ty Tucker	TDOT STID	615-532-7459	<u>Ty.tucker@tn.gov</u>
Nicholas Barnard	TDOT Traffic (Region 1)	865-594-2456	Nicholas.barnard@tn.gov
Keven Brown	TDOT Envir. (Region 1)	865-594-2437	Keven.brown@tn.gov
Dave Jordan	TDOT Design (Region 1)	865-594-0713	<u>Dave.jordan@tn.gov</u>
J. Eric Pickering	TDOT Survey (Region 1)	423-854-5128	James.pickering@tn.gov
David Harris	City of Kingsport	423-224-2416	Davidharris@kingsporttn.gov
Jason Brooks	City of Kingsport	423-229-9400	jasonbrooks@kingsporttn.gov
Tim Elsea	City of Kingsport	423-229-9400	timelsea@kingsporttn.gov
Shap Stiles	Gresham Smith	865-299-6138	Shap.stiles@greshamsmith.com
Matthew Giles	Gresham Smith	865-299-6151	Matthew.giles@greshamsmith.com

# NATIONAL BRIDGE INVENTORY TENNESSEE INVENTORY AND APPRAISAL REPORT

BRIDGE ID NUMBER: 37\$R0010037



COUNTY: HAWKINS

BRIDGE OWNER: STATE OF TENNESSEE ROUTE: SR001 FIPS CODE: 39560 SPECIAL CASE: 0 ROAD NAME: W. STONE DR. COUNTY SEQUENCE: 1 CROSSING: NORTH FORK HOLSTON RIVER LOG MILE: 41.30 LOCATION: ON CO LN SUFFICIENCY RATING: 33.1 IDENTIFICATION CLASSIFICATION = (16a,b) LATITUDE: (112) MEETS NBIS BRIDGE LENGTH: 36.55403 DEGREES YES (17a,b) LONGITUDE: (104) NATIONAL HIGHWAY SYSTEM: 82.61585 DEGREES **NHS ROUTE** (98a) BORDER BRIDGE STATE CODE: N/A (26) FUNCTIONAL CLASS: **URBAN PRINCIPAL ARTERIAL** (98b) PERCENT SHARE: N/A (101) PARALLEL BRIDGE: **RIGHT LANE BRIDGE** (99) BORDER BRIDGE NUMBER: (102) TRAFFIC DIR: **NOT APPLICABLE** 1-WAY TRAFFIC (103) TEMPORARY BRIDGE: **NOT APPLICABLE** BRIDGE TYPE AND MATERIAL = (110) NATIONAL TRUCK ROUTE: NOT ON TRUCK NETWORK (43a) MAIN SPAN MATERIAL: CONCRETE CONTINUOUS HISTORICAL SIGNIFICANCE HAS (37) HISTORICAL CLASS: (44a) APPR SPAN MATERIAL: CONCRETE **NOT BEEN DETERMINED** CONDITION RATINGS = (45) NUMBER OF MAIN SPANS: (58) DECK: 5 (46) NUMBER OF APPROACH SPANS: 8 (59) SUPERSTRUCTURE: 5 (107) TYPE OF DECK: **CONCRETE CAST-IN-PLACE** (60) SUBSTRUCTURE: (108) TYPE OF WEARING SURFACE AND DECK PROTECTION: (61) STREAM CHANNEL AND CHANNEL PROTECTION: 6 A) TYPE OF SURFACE: **ASPHALT** (62) CULVERT CONDITION (IF APPLICABLE): B) TYPE MEMBRANE: NONE DESIGN LOAD AND WEIGHT POSTING **EPOXY COATED REINFORCING** C) TYPE PROTECTION: (31) DESIGN LOADING: HS-20-44 AGE AND SERVICE = **ALL LEGAL LOADS** WEIGHT POSTING (2 AXLE VEHICLES): (27) YEAR THE BRIDGE WAS BUILT: 1962 WEIGHT POSTING (3 OR MORE AXLES): **ALL LEGAL LOADS** (106) YEAR THE BRIDGE WAS REHABILITATED: 1989 (70) BRIDGE POSTING CODE: (42a) SERVICE ON BRIDGE: **HIGHWAY** (41) WT POSTING STATUS: **WEIGHT POSTED HIGHWAY-WATERWAY** (42b) UNDER BRIDGE: APPRAISAL (28a) NUMBER OF LANES CARRIED BY BRIDGE: 2 (67) STRUCTURAL EVALUATION: (28b) NUMBER OF LANES UNDER THE BRIDGE: 2 (68) DECK GEOMETRY: GEOMETRIC DATA (69) UNDERCLEARANCE RATING: 4 (48) MAXIMUM SPAN LENGTH: 89.9 FT (71) WATERWAY ADEQUACY: 7 (49) TOTAL BRIDGE LENGTH: 591.9 FT (72) APPROACH ROADWAY ALIGNMENT: 8 (50a) LEFT SIDEWALK WIDTH: 4.9 FT (36) TRAFFIC SAFETY FEATURES: 1000 (50b) RIGHT SIDEWALK WIDTH: 4.9 FT (113) SCOUR CONDITION RATING: 8 (51) BRIDGE CURB TO CURB WIDTH: 27.9 FT RECOMMENDED IMPROVEMENTS (52) BRIDGE OUT TO OUT WIDTH: 39 FT (75) TYPE OF WORK: **BRIDGE WIDENING (NO DECK REPAIRS** (32) APPROACH ROADWAY (W/ SHLDS) WIDTH: 45.9 FT **NEEDED)** (76) LENGTH OF BRIDGE IMPROVEMENT: 591.9 FT (33) BRIDGE MEDIAN: **CLOSED MEDIAN - NO BARRIER** (94) BRIDGE IMPROVEMENT COST: \$1,964,000.00 (34) BRIDGE SKEW: 0 DEGREES (95) ROADWAY IMPROVEMENT COST: \$197,000.00 (35) BRIDGE FLARE: **NO FLARE** TOTAL PROJECT COST: \$2,947,000.00 (520) MIN VERTICAL CLEARANCE OVER RD: NO RESTRICTION (97) YEAR OF IMPROVEMENT COST ESTIMATE: 2021 (47) MIN HORIZONTAL CLEARANCE ON ROADWAY: 27.9 FT **HIGHWAY BENEATH BRIDGE** INSPECTION DATES (54a) VERT UNDERCLR: (54b) MIN VERTICAL UNDERCLEARANCE: (90) DATE OF LAST REGULAR INSPECTION: 8/18/2021 39.99 FT 24 (55a) HORZ UNDERCLR: **HIGHWAY BENEATH BRIDGE** (91) REGULAR INSPECTION FREQUENCY (MONTHS): (55b) MIN HORZ UNDERCLR ON RIGHT: (93b) DATE OF LAST UNDERWATER INSP (MO/YR): N/A (56) MIN HORZ UNDERCLR ON LEFT: **NOT APPLICABLE** (92b) UNDERWATER INSP FREQUENCY (MONTHS): Ν NAVIGATION DATA (93c) DATE OF SPECIAL INSPECTION (MO/YR): 08/2021 (38) NAV CONTROL: **NO NAVIGATION CONTROL** (92c) SPECIAL INSP FREQUENCY (MONTHS): Y12 (39) NAVIGATION VERTICAL CLEARANCE: N/A PRODUCED PURSUANT TO (116) LIFT BRIDGE VERT CLEARANCE: N/A PUBLIC RECORDS REQUEST (40) NAVIGATION HORZ CLEARANCE: N/A

# NATIONAL BRIDGE INVENTORY TENNESSEE INVENTORY AND APPRAISAL REPORT

BRIDGE ID NUMBER: 37SR0010038

BRIDGE OWNER: STATE OF TENNESSEE



COUNTY: HAWKINS

ROUTE: SR001


FIPS CODE: 39560 SPECIAL CASE: 0 ROAD NAME: W. STONE DR. COUNTY SEQUENCE: 1 CROSSING: NORTH FORK HOLSTON RIVER LOG MILE: 41.30 LOCATION: ON CO. LINE SUFFICIENCY RATING: 49.8 - IDENTIFICATION CLASSIFICATION = (16a,b) LATITUDE: (112) MEETS NBIS BRIDGE LENGTH: YES 36.55398 DEGREES (17a,b) LONGITUDE: (104) NATIONAL HIGHWAY SYSTEM: 82.61597 DEGREES **NHS ROUTE** (98a) BORDER BRIDGE STATE CODE: N/A (26) FUNCTIONAL CLASS: **URBAN PRINCIPAL ARTERIAL** (98b) PERCENT SHARE: N/A (101) PARALLEL BRIDGE: **LEFT LANE BRIDGE** (99) BORDER BRIDGE NUMBER: (102) TRAFFIC DIR: **NOT APPLICABLE** 1-WAY TRAFFIC (103) TEMPORARY BRIDGE: **NOT APPLICABLE** BRIDGE TYPE AND MATERIAL = (110) NATIONAL TRUCK ROUTE: NOT ON TRUCK NETWORK (43a) MAIN SPAN MATERIAL: CONCRETE CONTINUOUS HISTORICAL SIGNIFICANCE HAS (37) HISTORICAL CLASS: (44a) APPR SPAN MATERIAL: CONCRETE **NOT BEEN DETERMINED**  CONDITION RATINGS (45) NUMBER OF MAIN SPANS: (58) DECK: 4 (46) NUMBER OF APPROACH SPANS: 8 (59) SUPERSTRUCTURE: 5 (107) TYPE OF DECK: **CONCRETE CAST-IN-PLACE** (60) SUBSTRUCTURE: 5 (108) TYPE OF WEARING SURFACE AND DECK PROTECTION: (61) STREAM CHANNEL AND CHANNEL PROTECTION: 6 A) TYPE OF SURFACE: **ASPHALT** (62) CULVERT CONDITION (IF APPLICABLE): N B) TYPE MEMBRANE: NONE **DESIGN LOAD AND WEIGHT POSTING EPOXY COATED REINFORCING** C) TYPE PROTECTION: (31) DESIGN LOADING: HS-20-44 — AGE AND SERVICE = WEIGHT POSTING (2 AXLE VEHICLES): **ALL LEGAL LOADS** (27) YEAR THE BRIDGE WAS BUILT: 1962 WEIGHT POSTING (3 OR MORE AXLES): **ALL LEGAL LOADS** (106) YEAR THE BRIDGE WAS REHABILITATED: N/A (70) BRIDGE POSTING CODE: 5 (42a) SERVICE ON BRIDGE: **HIGHWAY** (41) WT POSTING STATUS: **WEIGHT POSTED** (42b) UNDER BRIDGE: **HIGHWAY-WATERWAY** APPRAISAL (28a) NUMBER OF LANES CARRIED BY BRIDGE: 2 (67) STRUCTURAL EVALUATION: 5 (28b) NUMBER OF LANES UNDER THE BRIDGE: 2 (68) DECK GEOMETRY: 3 GEOMETRIC DATA -(69) UNDERCLEARANCE RATING: 4 (48) MAXIMUM SPAN LENGTH: 89.9 FT (71) WATERWAY ADEQUACY: 7 (49) TOTAL BRIDGE LENGTH: 591.9 FT (72) APPROACH ROADWAY ALIGNMENT: 8 (50a) LEFT SIDEWALK WIDTH: 0.0 FT (36) TRAFFIC SAFETY FEATURES: 1000 (50b) RIGHT SIDEWALK WIDTH: 0.0 FT (113) SCOUR CONDITION RATING: 8 (51) BRIDGE CURB TO CURB WIDTH: 27.9 FT RECOMMENDED IMPROVEMENTS (52) BRIDGE OUT TO OUT WIDTH: 38.7 FT (75) TYPE OF WORK: **BRIDGE WIDENING WITH DECK REPAIR** (32) APPROACH ROADWAY (W/ SHLDS) WIDTH: 42.0 FT OR REPLACEMENT (76) LENGTH OF BRIDGE IMPROVEMENT: 591.9 FT (33) BRIDGE MEDIAN: **OPEN MEDIAN** (94) BRIDGE IMPROVEMENT COST: \$1,163,000.00 (34) BRIDGE SKEW: 0 DEGREES (95) ROADWAY IMPROVEMENT COST: \$117,000.00 (35) BRIDGE FLARE: **NO FLARE** TOTAL PROJECT COST: \$1,745,000.00 (520) MIN VERTICAL CLEARANCE OVER RD: NO RESTRICTION (97) YEAR OF IMPROVEMENT COST ESTIMATE: 2021 (47) MIN HORIZONTAL CLEARANCE ON ROADWAY: 27.9 FT INSPECTION DATES (54a) VERT UNDERCLR: **HIGHWAY BENEATH BRIDGE** (54b) MIN VERTICAL UNDERCLEARANCE: (90) DATE OF LAST REGULAR INSPECTION: 8/18/2021 39.99 FT (55a) HORZ UNDERCLR: **HIGHWAY BENEATH BRIDGE** (91) REGULAR INSPECTION FREQUENCY (MONTHS): 24 (55b) MIN HORZ UNDERCLR ON RIGHT: 6.23 FT (93b) DATE OF LAST UNDERWATER INSP (MO/YR): N/A (56) MIN HORZ UNDERCLR ON LEFT: **NOT APPLICABLE** (92b) UNDERWATER INSP FREQUENCY (MONTHS): Ν NAVIGATION DATA (93c) DATE OF SPECIAL INSPECTION (MO/YR): 08/2021 (38) NAV CONTROL: **NO NAVIGATION CONTROL** (92c) SPECIAL INSP FREQUENCY (MONTHS): Y12 (39) NAVIGATION VERTICAL CLEARANCE: N/A PRODUCED PURSUANT TO (116) LIFT BRIDGE VERT CLEARANCE: N/A PUBLIC RECORDS REQUEST (40) NAVIGATION HORZ CLEARANCE: N/A




From bridge looking downstream



From bridge looking upstream



Looking southeast at bridge inlet




Looking northwest at bridge outlet



Looking east along west bridge approach



Looking west along east bridge approach



From bridge looking west along roadway



From bridge looking east along roadway



West bridge abutment (inlet side) wall, piers and beams




East bridge abutment (inlet side) wall, piers and beams



Bridge ID stamped on beam near west abutment wall



Concrete and steel rail system on bridge



Gap between the two bridges



Utility lines north of bridge



Weight limit sign before beginning of bridge on east approach




Railroad bridge (owned by CSX) on east bridge approach

# National Flood Hazard Layer FIRMette




Basemap: USGS National Map: Orthoimagery: Data refreshed October, 2020



#### Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT



This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

point selected by the user and does not represent

an authoritative property location.

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 6/2/2021 at 3:17 PM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

# **StreamStats Report**

Region ID: TN

Workspace ID: TN20210602190337153000

Clicked Point (Latitude, Longitude): 36.55429, -82.61500

Time: 2021-06-02 14:03:58 -0500



Basin Characteristics						
Parameter Code	Parameter Description	Value	Unit			
CONTDA	Area that contributes flow to a point on a stream	725.97	square miles			
CSL10_85	Change in elevation divided by length between points 10 and 85 percent of distance along main channel to basin divide - main channel method not known	8.5	feet per mi			
CLIMFAC2YR	Two-year climate factor from Lichy and Karlinger (1990)	2.137	dimensionless			
DRNAREA	Area that drains to a point on a stream	725.97	square miles			

Parameter Code	Parameter Description	Value	Unit
RECESS	Number of days required for streamflow to recede one order of magnitude when hydrograph is plotted on logarithmic scale	72	days per log cycle
SOILPERM	Average Soil Permeability	2.853	inches per hour
PERMGTE2IN	Percent of area underlain by soils with permeability greater than or equal to 2 inches per hour	64.243	percent
HA1PCT	Percent of area within Hydrologic Area 1	100	percent
HA2PCT	Percent of area within Hydrologic Area 2	0	percent
НАЗРСТ	Percent of area within Hydrologic Area 3	0	percent
HA4PCT	Percent of area within Hydrologic Area 4	0	percent
TNCLFACT2	Tennessee climate factor, 2-year interval	2.137	dimensionless
TNSOILFAC	Tennessee soil factor, percentage of area underlain by a soil permeability greater than or equal to 2 inches per hour	64	percent

Peak-Flow Statistics Parameters [100.0 Percent (725 square miles) MultiVariable Area 1]

Parameter Code	Parameter Name	Value	Units	Min Limit	Max Limit
CONTDA	Contributing Drainage Area	725.97	square miles	0.2	9000
CSL10_85	Stream Slope 10 and 85 Method	8.5	feet per mi	3.29	950
CLIMFAC2YR	Tennessee Climate Factor 2 Year	2.137	dimensionless	2.06	2.32

Peak-Flow Statistics Flow Report [100.0 Percent (725 square miles) MultiVariable Area 1]

PII: Prediction Interval-Lower, PIu: Prediction Interval-Upper, SEp: Standard Error of Prediction, SE: Standard Error (other -- see report)

Statistic	Value	Unit	PII	Plu	SEp	Equiv. Yrs.
50-percent AEP flood	13600	ft^3/s	7300	25300	39.2	1.7
20-percent AEP flood	20300	ft^3/s	10900	37700	38.2	2.6
10-percent AEP flood	25100	ft^3/s	13300	47400	40.1	3.4

Statistic	Value	Unit	PII	Plu	SEp	Equiv. Yrs.
4-percent AEP flood	31700	ft^3/s	16200	62200	42.7	4.3
2-percent AEP flood	36700	ft^3/s	18000	74600	45.2	4.9
1-percent AEP flood	42200	ft^3/s	20000	89300	47.9	5.3
0.2-percent AEP flood	55500	ft^3/s	23700	130000	55.2	5.8

Peak-Flow Statistics Citations

Law, G.S., and Tasker G.D.,2003, Flood-Frequency Prediction Methods for Unregulated Streams of Tennessee, 2000: U.S. Geological Survey Water-Resources Investigations Report 03-4176, 79p. (http://pubs.usgs.gov/wri/wri034176/)

Low-Flow Statistics Parameters [100.0 Percent (725 square miles) Low Flow Central and East Regions 2009 5159]

Parameter Code	Parameter Name	Value	Units	Min Limit	Max Limit
DRNAREA	Drainage Area	725.97	square miles	1.3	14441
RECESS	Recession Index	72	days per log cycle	32	175
CLIMFAC2YR	Tennessee Climate Factor 2 Year	2.137	dimensionless	2.056	2.46
SOILPERM	Average Soil Permeability	2.853	inches per hour	0.45	9.72
PERMGTE2IN	Percent permeability gte 2 in per hr	64.243	percent	2	100

Low-Flow Statistics Flow Report [100.0 Percent (725 square miles) Low Flow Central and East Regions 2009 5159]

PII: Prediction Interval-Lower, Plu: Prediction Interval-Upper, SEp: Standard Error of Prediction, SE: Standard Error (other -- see report)

Statistic	Value	Unit	SEp
7 Day 10 Year Low Flow	86.2	ft^3/s	89
30 Day 5 Year Low Flow	129	ft^3/s	70.2

Low-Flow Statistics Citations

Law, G.S., Tasker, G.D., and Ladd, D.E., 2009, Streamflow-characteristic estimation methods for unregulated streams of Tennessee: U.S. Geological Survey Scientific Investigations

#### Report 2009-5159, 212 p., 1 pl. (http://pubs.usgs.gov/sir/2009/5159/)

Flow-Duration Statistics Parameters [100.0 Percent (725 square miles) Low Flow Central and East Regions 2009 5159]

Parameter Code	Parameter Name	Value	Units	Min Limit	Max Limit
DRNAREA	Drainage Area	725.97	square miles	1.3	14441
RECESS	Recession Index	72	days per log cycle	32	175
CLIMFAC2YR	Tennessee Climate Factor 2 Year	2.137	dimensionless	2.056	2.46
SOILPERM	Average Soil Permeability	2.853	inches per hour	0.45	9.72
PERMGTE2IN	Percent permeability gte 2 in per hr	64.243	percent	2	100

Flow-Duration Statistics Flow Report [100.0 Percent (725 square miles) Low Flow Central and East Regions 2009 5159]

PII: Prediction Interval-Lower, Plu: Prediction Interval-Upper, SEp: Standard Error of Prediction, SE: Standard Error (other -- see report)

Statistic	Value	Unit	SEp
99.5 Percent Duration	81.1	ft^3/s	86.4
99 Percent Duration	93.2	ft^3/s	78
98 Percent Duration	110	ft^3/s	72.2
95 Percent Duration	142	ft^3/s	66.3
90 Percent Duration	188	ft^3/s	60.2
80 Percent Duration	275	ft^3/s	54
70 Percent Duration	387	ft^3/s	50.7
60 Percent Duration	525	ft^3/s	48.7
50 Percent Duration	707	ft^3/s	42.9
40 Percent Duration	918	ft^3/s	36.1
30 Percent Duration	1170	ft^3/s	28.3
20 Percent Duration	1570	ft^3/s	23.3
10 Percent Duration	2380	ft^3/s	20.8

#### Flow-Duration Statistics Citations

Law, G.S., Tasker, G.D., and Ladd, D.E., 2009, Streamflow-characteristic estimation methods for unregulated streams of Tennessee: U.S. Geological Survey Scientific Investigations Report 2009–5159, 212 p., 1 pl. (http://pubs.usgs.gov/sir/2009/5159/)

Annual Flow Statistics Parameters [100.0 Percent (725 square miles) Low Flow Central and East Regions 2009 5159]

Parameter Code	Parameter Name	Value	Units	Min Limit	Max Limit
DRNAREA	Drainage Area	725.97	square miles	1.3	14441
CLIMFAC2YR	Tennessee Climate Factor 2 Year	2.137	dimensionless	2.056	2.46
SOILPERM	Average Soil Permeability	2.853	inches per hour	0.45	9.72

Annual Flow Statistics Flow Report [100.0 Percent (725 square miles) Low Flow Central and East Regions 2009 5159]

PII: Prediction Interval-Lower, Plu: Prediction Interval-Upper, SEp: Standard Error of Prediction, SE: Standard Error (other -- see report)

Statistic	Value	Unit	SEp
Mean Annual Flow	1100	ft^3/s	25.6

Annual Flow Statistics Citations

Law, G.S., Tasker, G.D., and Ladd, D.E., 2009, Streamflow-characteristic estimation methods for unregulated streams of Tennessee: U.S. Geological Survey Scientific Investigations Report 2009–5159, 212 p., 1 pl. (http://pubs.usgs.gov/sir/2009/5159/)

Seasonal Flow Statistics Parameters [100.0 Percent (725 square miles) Low Flow Central and East Regions 2009 5159]

Parameter Code	Parameter Name	Value	Units	Min Limit	Max Limit
DRNAREA	Drainage Area	725.97	square miles	1.3	14441
RECESS	Recession Index	72	days per log cycle	32	175

Parameter Code	Parameter Name	Value	Units	Min Limit	Max Limit
CLIMFAC2YR	Tennessee Climate Factor 2 Year	2.137	dimensionless	2.056	2.46
SOILPERM	Average Soil Permeability	2.853	inches per hour	0.45	9.72

Seasonal Flow Statistics Flow Report [100.0 Percent (725 square miles) Low Flow Central and East Regions 2009 5159]

PII: Prediction Interval-Lower, Plu: Prediction Interval-Upper, SEp: Standard Error of Prediction, SE: Standard Error (other -- see report)

Statistic	Value	Unit	SEp	
Summer Mean Flow	750	ft^3/s	43.1	

Seasonal Flow Statistics Citations

Law, G.S., Tasker, G.D., and Ladd, D.E.,2009, Streamflow-characteristic estimation methods for unregulated streams of Tennessee: U.S. Geological Survey Scientific Investigations Report 2009–5159, 212 p., 1 pl. (http://pubs.usgs.gov/sir/2009/5159/)

USGS Data Disclaimer: Unless otherwise stated, all data, metadata and related materials are considered to satisfy the quality standards relative to the purpose for which the data were collected. Although these data and associated metadata have been reviewed for accuracy and completeness and approved for release by the U.S. Geological Survey (USGS), no warranty expressed or implied is made regarding the display or utility of the data for other purposes, nor on all computer systems, nor shall the act of distribution constitute any such warranty.

USGS Software Disclaimer: This software has been approved for release by the U.S. Geological Survey (USGS). Although the software has been subjected to rigorous review, the USGS reserves the right to update the software as needed pursuant to further analysis and review. No warranty, expressed or implied, is made by the USGS or the U.S. Government as to the functionality of the software and related material nor shall the fact of release constitute any such warranty. Furthermore, the software is released on condition that neither the USGS nor the U.S. Government shall be held liable for any damages resulting from its authorized or unauthorized use.

USGS Product Names Disclaimer: Any use of trade, firm, or product names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

Application Version: 4.5.3

StreamStats Services Version: 1.2.22

NSS Services Version: 2.1.2

# TENNESSEE DEPARTMENT OF TRANSPORTATION STRATEGIC TRANSPORTATION INVESTMENTS DIVISION

PROJECT	NO.: 3	7070-0237-0	4			ROUTE:	S.R. 1				
COUNTY:	Н	IAWKINS					KINGSPORT				
PROJECT	PIN NUM	134 IBER: 134	134387.00								
PROJECT DESCRIPTION:			BRIDGE AND APPROACHES OVER NORTH FORK HOLSTON RIVER @								
			L.M. 41.30.								
DIVISION REQUESTING:											
			PAVEMENT DESIGN								
MAINTE	NANCE		STRUCTURES								
S.T.I.D.			SURVEY & ROADWAY DESIGN								
PROG. DEVELOPMENT & ADM. TRAFFIC SIGNAL DESIGN								_			
PUBLIC TRANS. & AERO. U OTHER ULL OT											
YEAR PROJECT PROGRAMMED FOR CONSTRUCTION:											
PROJECTED LETTING DATE:											
TRAFFIC ASSIGNMENT:											
						DES	SIGN	DES	SIGN		
							ROA	DWAY	AVERAGE		
BASE Y	EAR		DESIGN YEAR					UCKS	DAILY LOADS		
AADT	YEAR	AADT	DHV	%	YEAR	DIR.DIST.	DHV	AADT	FLEX	RIGID	
34,820	2026	48,750	4,875	10	2046	55-45	2	3			
REQUESTED BY:		NAME ETHAN MESSIMORE			1		DATE	1/21/21			
•		DIVISION								_	
		ADDRESS									
		TIDDICES			ETN 3724						
							٦.				
REVIEWED BY: DEBBI H			howard <u>Debbi Howard</u> date <u>1/21/2021</u>								
			PORTATION MANAGER 1								
		SUITE 1000	JAMES K. I	POLK	BUILDING	G					
A DDD OX 75	TONK ARM	Tony Armstrong									
			rmstrong Tony Armstrong date 1/21/2021								
			PORTATION MANAGER 2 000, JAMES K. POLK BUILDING								
		SUITE 1000,	JAIVIES K. I	OLK	POILDIM	J					
<u>COMMENTS:</u>											
FURNISH THE 2026-2046 TRAFFIC DATA.											

THIS TRAFFIC IS BASED ON A SULLIVAN COUNTY CYCLE COUNT. THE DESIGN YEAR TRAFFIC IS BASED ON GROWTH RATE FROM THE KINGSPORT MPO COMPUTER ASSIGNMENT MODEL.

#### DHV'S ARE NOT REQUIRED FOR SIDE ROADS LESS THAN 1000 AADT.