Rev. 04-14-14		HWAY BRIDG N OF ACTION			<b>TRANSPORTATION</b>
BRIDGE ROA CR LA	IUMBER: 080A3490001 OWNER: CANNON COUNTY D NAME: YOUNG BRIDGE LN OSSING: EAST FORK STONES RIVE TITUDE:: N 35.83025 DEGREES GITUDE: W 86.00748 DEGREES	6		COUNTY: ROUTE: SPECIAL CASE: COUNTY SEQUENCE: LOG MILE: YEAR BUILT:	0 1 0.00
		TYPE OF SUPER	STRUCTURE -		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM (	DR GIRDER	APPR. SPAN:	NOT APPLICABLE	
ABUTMENTS: BENTS: PIERS:	MASONRY OR CONCRETE BLOCK NOT APPLICABLE NOT APPLICABLE	<ul> <li>TYPE OF SUBST ABUTMENTS ON UI</li> </ul>		DATION	
		SCOUR EVAL			
during signifi	inknown foundations. Risk of so icant flood events. Rip-rap prote /stem are needed.				
		INSPECTION PRODUCTION PRODUCTURA PRODUCTU	OCEDURES -		
What Initiat	ed the Call-out Inspection?	[] TDOT Di		al Maintenance Personn forcement Personnel	el

## Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
  - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.
  - 2. Check for plumb of piers or bents.
- [ ] Check for embankment erosion
- [ ] Check for drift build-up on piers or bents
- [ ] Check pier exposure, if possible, and compare to previous inspection
- [ ] Review the latest bridge inspection report versus current field conditions

## If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [ ] Contact: (1) District Maintenance Supervisor ( if bridge is State maintained )
  - (2) City or County Highway Maintenance Official ( if bridge is not State maintained )
  - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
  - (4) TDOT Regional Bridge Engineer
- [ ] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

P	U	Bl		C	Α-	ТΙ	Ο	Ν	D	A	ΤE
•			-	<b>U</b>		•••	~		-		

21-Apr-14



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(615) 563-2320
HWY. CHIEF ADMINISTRATOR'S OFFICE	(615) 563-4213
COUNTY SHERIFF'S OFFICE	(615) 563-4322

[ ] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

COMMENTS:

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

Range Pole

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)

