HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 390A2640001

BRIDGE OWNER: HENDERSON COUNTY ROAD NAME: BELTON ROBISON RD

TENN DEPT OF TRANSPORTATION

COUNTY: HENDERSON

ROUTE: 0A264

SPECIAL CASE: 0

CROSSING: BEECH RIVER	COUNTY SEQUENCE: 1	
LATITUDE:: N 35.61378 DEGREES LOG MILE: 1.83		
LONGITUDE: W 88.29553 DEGREES	YEAR BUILT: 1975	
TYPE OF SUPERSTRUCTURE		
MAIN SPAN: STEEL - STRINGER/MULTI-BEAM OR GIRDER APPR. SPAN:	NOT APPLICABLE	
TYPE OF SUBSTRUCTURE		
ABUTMENTS: TIMBER CAP ON TIMBER PILE FOUNDATION		
BENTS: TIMBER PILE BENT ON PILE FOUNDATION		
PIERS: NOT APPLICABLE		
COOLID FIVAL HATION		
SCOUR EVALUATION -	La La Caracteria de la	
Bridge is scour critical; bridge foundations determined to be unstable for cal countermeasures are installed but they are needed.	Iculated scour conditions. No scour	
countermeasures are instance but they are needed.		
INSPECTION PROCEDURES —		
What Initiated the Call-out Inspection? [] BridgeWatch Alert		
• •	al Maintenance Personnel	
[] THP or Local Law Enf		
[] Other:		
Things to check on a bridge during floods:		
[] - Span movement - horizontally as well as vertically		
1. Check displacement / deflection along curb line, both bridge	e rails and outer edge of bridge deck.	
2. Check for plumb of piers or bents.		
[] - Check for embankment erosion		
[] - Check for drift build-up on piers or bents		
[] - Check pier exposure, if possible, and compare to previous inspe	ection	
[] - Review the latest bridge inspection report versus current field conditions		
If Closure is recommended:		
[] - Stay at bridge with vehicle pulled across road until bridge is sec		
County or City Maintenance Personnel. Use Barricade Tape, traft temporary measures to warn motorists to stay off of the bridge		
be properly closed and barricaded.	until such time as the bridge may	
[] - Contact: (1) District Maintenance Supervisor (if bridge is State	e maintained)	
(2) City or County Highway Maintenance Official (if br	•	
(3) Tennessee Highway Patrol and/or local law enforce	,	
(4) TDOT Regional Bridge Engineer	P. P	
[] - The Bridge should remain closed until the water recedes and a	daylight visual inspection is made	
by a TDOT bridge inspection team.		

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	e District maintenance or local highway maintenance dge on the selected detour route shall be checked
[] - The bridge can be re-opened only after a TDOT units and they are determined to be structurall	
CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(731) 968-0122
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 968-9201
COUNTY SHERIFF'S OFFICE	(731) 968-7777
 Summarize and submit findings from the inspe The report shall include the date and time of th as appropriate, photographs of the bridge and scouring has occurred, the report shall also be 	e inspection, a brief summary of findings and, stream channel measurements. If significant
COMMENTS:	
Suggested List of Equipment to conduct the Inspect	on:
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	
SAFETY HAZARD KEEP	AWAY
A Barricade Tape Dispenser with serrated cutter A roll of Duct Tape	
A foil of Duct Tape	

Traffic Cones - Minimum of four (4)

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone