HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 52S42810013
BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: PETERSBURG-CHESTNUT RIDGE

CROSSING: HANNAH GAP BRANCH
LATITUDE:: N 35.31643 DEGREES
ONGITUDE: W 86.58038 DEGREES

COUNTY: LINCOLN
ROUTE: SR129
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 3.77

	IGITUDE: W 86.58038 DEGREES		
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:			
		TYPE OF SUBSTRUCTURE -	
		NT ON CONCRETE SPREAD FOOTING FOUNDATION	
BENTS: PIERS:	NOT APPLICABLE	CONCRETE SPREAD FOOTING FOUNDATION	
PIERO.	CONCRETE SOLID SHAFT PIER ON	CONCRETE SPREAD FOOTING FOUNDATION	
		SCOUR EVALUATION ————————————————————————————————————	
		our cannot be determined. The bridge shall be monitored for distress e in lieu of installing scour countermeasures.	
		INSPECTION PROCEDURES -	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
1. C 2. C [] - Chec [] - Chec	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a	n along curb line, both bridge rails and outer edge of bridge deck. nts.	
<u>If Closure is</u>	recommended:		
Coun temp] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.		
[] - Conta	act: (1) District Maintenance S	supervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
		atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	_	
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



[]-		ate District maintenance or local highway maintenance ridge on the selected detour route shall be checked	
[]-	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
	CONTACT PERSONNEL:	TELEPHONE NUMBER:	
	REGION BRIDGE ENGINEER	(615) 476-8860	
	DISTRICT MAINTENANCE SUPERVISOR	(931) 242-6042	
	TENNESSEE HIGHWAY PATROL	(931) 766-1425	
	The report shall include the date and time of t	ection to BridgeWatch scour monitoring system. The inspection, a brief summary of findings and, It stream channel measurements. If significant The copied to Bridge Inspection Headquarters.	
COMM	ENTS:		
Sugge	ested List of Equipment to conduct the Inspec	ction:	
Latest	Bridge Inspection Report		
	POA Report with the above Checklist		
_	e Design Plans, if available		
•	measure with weight		
Plumb			
Range			
A 100	Foot Roll of yellow Polyethylene Barricade 1		
	SAFETY HAZARD KEE	AWAY	

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)