


SECTION A-A



SECTION B-B




SECTION D-D

- ① DEPTH MEASUREMENT MADE FROM TOP OF GRATE TO OUTLET FLOW ELEVATION BASED ON INLET AND OUTLET PIPES BEING THE SAME DIAMETER, IF OUTLET PIPE IS GREATER ADJUSTMENT IN DEPTHS MUST BE MADE TO ACCOMMODATE THIS SITUATION.
- ② TO DETERMINE FLOOR OF CATCH BASIN ELEVATION, WHEN INLET AND OUTLET PIPES ARE THE SAME SIZE, ADD PIPE WALL THICKNESS PLUS 40 mm TO THE ABOVE MINIMUM DEPTHS.

- ① CUT-OUT HOLES FOR PRECAST STRUCTURES TO BE CORED OR FORMED IN ORDER TO OBTAIN A SMOOTH EDGED HOLE. SCORED OR ETCHED HOLES WITH REINFORCING STEEL LEFT UNCUT WILL NOT BE PERMITTED.
- ② TO BE USED IN FRONT AND BACK WALLS ONLY.

GENERAL NOTES

- 

MINOR REVISION -- FHWA
APPROVAL NOT REQUIRED.

STANDARD RECTANGULAR
CONCRETE NO. 29
CATCH BASIN
(FOR USE WITH 100 mm
MOUNTABLE CURB)

11-1-95	DM-CB-29S
---------	-----------