

POST


Q JOINT POST

RAIL BOLT SLOT

23 mm x 29 mm

€ JOINT POST

RAIL BOLT SLOT



RUB RAIL SPLICE DETAIL

GENERAL NOTES

- (A) CORRUGATED SHEET STEEL BEAMS SHALL CONFORM TO THE CURRENT REQUIREMENTS OF AASHTO M180, CLASS A, TYPE 2 . RAIL MATERIAL SHALL HAVE A YIELD STRENGTH OF 345 MEGAPASCALS AND A TENSILE STRENGTH OF 483 MEGAPASCALS.
- (B) RUB RAILS AND RUB RAIL SPLICE PLATES SHALL CONFORM TO ASTM A36M AND SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A123.
- © WHERE GUARDRAIL IS TO BE PLACED ON A CURVE WITH A RADIUS LESS THAN 45 m, THE RAIL SECTION SHALL BE SHOP-FORMED TO THE REQUIRED RADIUS.
- (D) SEE THE "RDM-TS" STANDARD SERIES FOR GUARDRAIL PLACEMENT.

TYPE 3: 3.810 m SPACING

(E) ITEM NUMBERS FOR PAYMENT AS DETAILED ON THESE "SM-GR" SERIES OF DRAWINGS ARE AS FOLLOWS:

ITEM NO.	DESCRIPTION	ON DWG NO.
705M01.01 705M01.04 705M02.01 705M02.02 705M03.01 705M03.02 705M03.03 705M03.04 705M04.02 705M04.03 705M04.03 705M04.04	GUARDRAIL AT BRIDGE ENDS METAL BEAM GUARD FENCE SINGLE GUARDRAIL WITH RUB-RAIL (TYPE 2) SINGLE GUARDRAIL WITH RUB-RAIL (TYPE 2) MEDIAN DIVIDER GUARDRAIL W/RUB-RAIL (TYPE 2) MEDIAN DIVIDER GUARDRAIL (TYPE 2) MEDIAN DIVIDER GUARDRAIL (TYPE 2)(675 mm MT. HT.) MEDIAN DIVIDER GUARDRAIL AT CONCRETE BARRIER GUARDRAIL TERMINAL (TYPE 12) GUARDRAIL TERMINAL (TYPE 13) GUARDRAIL TERMINAL (TYPE 21) GUARDRAIL TERMINAL (TYPE 21) GUARDRAIL TERMINAL (TYPE 21) TANGENT ENERGY ABSORBING TERMINAL (NCHRP 350 - TL3)	SM-GR-17 & SM-GR-23 SM-GR-22 & DM-CE-3 SM-GR-13 & SM-GR-18 SM-GR-13 & SM-GR-18 SM-GR-13 & SM-GR-18 SM-GR-13 & SM-GR-18 SM-GR-13 & SM-GR-18 SM-GR-19 SM-GR-19 SM-GR-19 SM-GR-26 SM-GR-18 SM-GR-32, SM-GR-35 & SM-GR-40
	3 mm SPACING 5 m SPACING	



ALL UNITS ARE IN MILLIMETERS UNLESS NOTED OTHERWISE.

■ REV. 11-1-95: CHANGED TO METRIC. REV. 7-29-98: MODIFIED GENERAL NOTE (F).

REV. 9-5-98: MODIFIED GENERAL

■ REV. 10-26-99: DELETED BACK UP

REV. 9-5-00: IN GENERAL NOTES CORRECTED NOTE (F).

REV. 5-27-01: IN GENERAL NOTE (F) CHANGED ITEM NUMBERS OF GUARDRAIL

TO CONCUR WITH NEW PAY ITEM

FOR ITEM NO. 705M04.07.

■ REV. 9-11-02: DELETED ITEM

■ REV. 9-5-03: CHANGED GENERAL

NOTE (A). DELETED GENERAL NOTE

B. RENUMBERED REMAINING GENERAL

NO. 705M01.02.

■ REV. 9-5-01: CORRECTED DESCRIPTION

PLATE DETAILS.

SYSTEM.

NOTES.

MINOR REVISION -- FHWA APPROVAL NOT REQUIRED.

STATE OF TENNESSEE DEPARTMENT OF TRANSPORTATION

W-BEAM & THRIE BEAM BARRIER RAIL AND RUB RAIL ALTERNATES

11-1-95 | SM-GR-11

FRONT ELEVATION "W"-BEAM

¢ POST

PLANS VIEW W-BEAM OR THRIE RAIL

THRIE-RAIL ELEMENT IS FURNISHED IN LENGTHS 4.128 m OR 7.938 m AASHTO M180, CLASS "A", TYPE 2

1.905 m

POST BOLT SLOT-

1.905 m

POST BOLT SLOT

-RAIL BOLT SLOT

POST BOLT SLOT

 $19 \text{ mm} \times 64 \text{ mm}$

RAIL BOLT SLOT

POST BOLT SLOT

 $19 \text{ mm} \times 64 \text{ mm}$

€ INTERMEDIATE

DIRECTION OF TRAFFIC

1.905 m

JOINT

OVERLAP___

POST

FRONT ELEVATION "THRIE" RAIL

INTERMEDIATE

DIRECTION OF TRAFFIC

1.905 m

JOINT

OVERLAP-

W-BEAM ELEMENT IS FURNISHED IN LENGTHS 4.128 m OR 7.938 m AASHTO M180, CLASS "A", TYPE 2

POST