HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 06043900001 BRIDGE OWNER: CITY OF CLEVELAND ROAD NAME: INMAN ST SW

CROSSING: BRANCH

LATITUDE:: N 35.16183 DEGREES

COUNTY: BRADLEY ROUTE: 04390 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 0.13

LON	NGITUDE: W 84.88102 DEGREES	YEAR BUILT: 1950
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE CONTINUOUS - CULVE FRAME CULVERTS)	RT (INCLUDES APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE BOX TYPE ON CONCR	ETE SPREAD FOOTING FOUNDATION
BENTS:	NOT APPLICABLE	
PIERS:	PIER WALL FOR CONCRETE BOX	ON CONCRETE SPREAD FOOTING FOUNDATION
		SCOUR EVALUATION
Bridge has I	inknown foundations. Risk of so	our cannot be determined. The bridge shall be monitored for distress
		e in lieu of installing scour countermeasures.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
	·	[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
1. 0 2. 0 [] - Chec [] - Chec	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a	n along curb line, both bridge rails and outer edge of bridge deck. nts.
lf Closure is	recommended:	
[] - Stay : Cour temp	at bridge with vehicle pulled a nty or City Maintenance Perso	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State maintained)
		y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed until the water recedes and a daylight visual inspection is made	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	State District maintenance or local highway maintenance y bridge on the selected detour route shall be checked	
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
CITY MAYOR'S OFFICE	(423) 472-4551	
CITY ENGINEER'S OFFICE	(423) 479-8153	
The report shall include the date and time as appropriate, photographs of the bridge	nspection to BridgeWatch scour monitoring system. of the inspection, a brief summary of findings and, and stream channel measurements. If significant o be copied to Bridge Inspection Headquarters.	
COMMENTS:		
Suggested List of Equipment to conduct the Ins	pection:	
Latest Bridge Inspection Report		
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricad	le Tape printed with the following message:	
SAFETY HAZARD K	FED AWAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)