## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 060A8610003
BRIDGE OWNER: BRADLEY COUNTY

ROAD NAME: HUNT RD

CROSSING: COAHULLA CREEK

LATITUDE:: N 35.02797 DEGREES LONGITUDE: W 84.84700 DEGREES

COUNTY: BRADLEY
ROUTE: 0A861
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 5.57

LON	NGITUDE: W 84.84700 DEGREES		YEAR BUILT: 1989
		TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	PRESTRESSED CONCRETE CONTII STRINGER/MULTI-BEAM OR GIRDE		NOT APPLICABLE
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	BUTMENTS: CONCRETE STUB ABUTMENT ON STEEL PILE FOUNDATION		
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE HAMMERHEAD PIER OF	N STEEL PILE FOUNDATION	
		SCOUR EVALUATION =	
	our critical; bridge foundations de ling scour countermeasures.	termined to be unstable for cal	culated scour conditions. Monitor bridge in
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
	•	[ ] TDOT District or Loca	al Maintenance Personnel
		[ ] THP or Local Law En	forcement Personnel
		[ ] Other:	
1. C 2. C [ ] - Chec [ ] - Chec	movement - horizontally as we Check displacement / deflection Check for plumb of piers or bea k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, ar ew the latest bridge inspection	n along curb line, both bridgents. bents nd compare to previous inspe	
<u>lf Closure is</u>	recommended:		
Coun temp	Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as emporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.		
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State	maintained )
	(2) City or County Highwa	y Maintenance Official ( if br	ridge is not State maintained )
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	•	
	he Bridge should remain closed until the water recedes and a daylight visual inspection is made y a TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked		
<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(423) 728-7141		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 728-7006		
COUNTY SHERIFF'S OFFICE	(423) 728-7301		
The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.  COMMENTS:			
Suggested List of Equipment to conduct the Inspec	tion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade T			
SAFETY HAZARD KEEP	PAWAY		
A Barricade Tape Dispenser with serrated cutter			

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

A roll of Duct Tape