## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 310A5100001
BRIDGE OWNER: GRUNDY COUNTY
ROAD NAME: SCRUGGS LN.
CROSSING: SMALL BRANCH

LATITUDE:: N 35.49315 DEGREES
LONGITUDE: W 85.65138 DEGREES

COUNTY: GRUNDY
ROUTE: 0A510
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.10
YEAR BUILT: 1945

20.	1011052: 11 00:00100 DIGINIZE	•		12/11 JOIL 11 10-10
		TYPE OF SU	PERSTRUCTURE -	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	R GIRDER	APPR. SPAN:	NOT APPLICABLE
		TYPE OF S	UBSTRUCTURE =	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME			
BENTS:	NOT APPLICABLE		MICHORDANION	
PIERS:	NOT APPLICABLE			
	NOT AT LIGABLE			
			EVALUATION -	
	unknown foundations. Risk of sco ricant flood events. Monitor bridge			bridge shall be monitored for distress ntermeasures.
		- INSPECTIO	N PROCEDURES •	
What Initiat	ed the Call-out Inspection?	[ ] Brid	geWatch Alert	
Triat initiated the can ear mepodiem.			_	al Maintenance Personnel
				forcement Personnel
1. 0 2. 0 [ ] - Chec [ ] - Chec	movement - horizontally as we have displacement / deflection check for plumb of piers or best for embankment erosion ek for drift build-up on piers or ek pier exposure, if possible, are the latest bridge inspection	n along cur nts. bents nd compare	b line, both bridg to previous insp	
If Closure is	recommended:			
Cour temp	nty or City Maintenance Persor	nnel. Use Ba rists to stay	rricade Tape, tra	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	Supervisor (	if bridge is State	e maintained )
	(2) City or County Highwa	y Maintena	nce Official ( if b	ridge is not State maintained )
	(3) Tennessee Highway P	atrol and/or	local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer		
	] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	h State District maintenance or local highway maintenance any bridge on the selected detour route shall be checked			
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:			
COUNTY MAYOR'S OFFICE	(931) 692-3718			
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 592-3751			
COUNTY SHERIFF'S OFFICE	(931) 692-3466			
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.				
COMMENTS:				
Suggested List of Equipment to conduct the In	spection:			
Latest Bridge Inspection Report				
Scour POA Report with the above Checklist				
Bridge Design Plans, if available				
Tape measure with weight				
Plumb bob				
Range Pole				
A 1000 Foot Roll of yellow Polyethylene Barrica				
SAFETY HAZARD	KEEP AWAY			

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24