HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 360A3610001
BRIDGE OWNER: HARDIN COUNTY
ROAD NAME: LEATH RD

CROSSING: LEATH CREEK

LATITUDE:: N 35.06000 DEGREES LONGITUDE: W 88.30381 DEGREES

COUNTY: HARDIN
ROUTE: 0A361
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.08
YEAR BUILT: 1070

LON	NGHODE. W 66.30361 DEGREES	TEAN BOILT. 1970
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FOU	INDATION
BENTS:	NOT APPLICABLE	
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
		our cannot be determined. The bridge shall be monitored for distress e in lieu of installing scour countermeasures.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		THP or Local Law Enforcement Personnel
		[] Other:
Things to c	heck on a bridge during floods	<u>s:</u>
[] - Span	n movement - horizontally as w	ell as vertically
	-	n along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	
	ck for embankment erosion	
	k for drift build-up on piers or	bents
	· · · · ·	nd compare to previous inspection
Review the latest bridge inspection report versus current field conditions		
<u>If Closure is</u>	s recommended:	
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
• • •		Supervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed u TDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	State District maintenance or local highway maintenance y bridge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 925-9078		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 925-4993		
COUNTY SHERIFF'S OFFICE	(731) 925-3377		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Insp Latest Bridge Inspection Report	pection:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricad			
SAFFTY HAZARD KE	-EP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24