HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 570A3570001
BRIDGE OWNER: MADISON COUNTY
ROAD NAME: SEAVERS RD.
CROSSING: BRANCH

LATITUDE:: N 35.51917 DEGREES
LONGITUDE: W -88.80978 DEGREES

COUNTY: MADISON
ROUTE: 0A357
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.790
YEAR BUILT: 2001

		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - BOX CULVERT	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE BOX CULVERT	
BENTS:	NOT APPLICABLE	
PIERS:	CONCRETE - BOX CULVERT	
		SCOUR EVALUATION
	our critical; bridge foundations de sures are installed but they are r	etermined to be unstable for calculated scour conditions. No scour needed.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
Things to c	heck on a bridge during flood	<u>s:</u>
[] - Span	movement - horizontally as w	vell as vertically
1. 0	heck displacement / deflectio	on along curb line, both bridge rails and outer edge of bridge deck.
2. 0	Check for plumb of piers or be	nts.
[] - Chec	k for embankment erosion	
[] - Chec	k for drift build-up on piers or	bents
[] - Chec	k pier exposure, if possible, a	nd compare to previous inspection
[] - Revie	w the latest bridge inspection	report versus current field conditions
<u>It Closure is</u>	recommended:	
Coun temp	nty or City Maintenance Person	ncross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may.
		Supervisor (if bridge is State maintained)
	(2) City or County Highwa	ay Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	e Engineer
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	state District maintenance or local highway maintenance bridge on the selected detour route shall be checked	
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR'S OFFICE	(731) 423-6020	
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 422-1651	
COUNTY SHERIFF'S OFFICE	(731) 423-6000	
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 		
COMMENTS:		
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report	ection:	
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricade		
SAFETY HAZARD KEI	EP AWAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

05-May-25