## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 73SR0290003

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: **S ROANE ST**CROSSING: **EMORY RIVER** 

LATITUDE:: N 35.92887 DEGREES
LONGITUDE: W 84.55697 DEGREES

COUNTY: ROANE
ROUTE: SR029
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 7.48
VEAP BUILT: 1957

LON	NGITUDE: W 84.55697 DEGREES	3	YEAR BUILT: 1957
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	STEEL CONTINUOUS - STRINGER/I	MULTI-BEAM OR APPR. SPAN:	PRESTRESSED CONCRETE - BOX BEAM OR GIRDERS - SINGLE OR SPREAD
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON S	STEEL PILE FOUNDATION	
BENTS:	NTS: CONCRETE COLUMN FOUR OR MORE POST BENT ON STEEL PILE FOUNDATION		
PIERS:	CONCRETE COLUMNS WITH SOLI	O WEB WALL (DUMB BELL) ON STE	EL PILE FOUNDATION
		SCOUR EVALUATION	
	our critical; bridge foundations de ling scour countermeasures.		culated scour conditions. Monitor bridge in
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
	·		al Maintenance Personnel
		[ ] THP or Local Law En	forcement Personnel
		[ ] Other:	
[ ] - Span 1. C 2. C [ ] - Chec [ ] - Chec	heck on a bridge during floods movement - horizontally as we check displacement / deflection check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, and ew the latest bridge inspection	ell as vertically n along curb line, both bridg nts. bents nd compare to previous insp	
<u>If Closure is</u>	recommended:		
Coun temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	Supervisor ( if bridge is State	maintained )
	(2) City or County Highwa	y Maintenance Official ( if b	ridge is not State maintained )
	(3) Tennessee Highway P	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	e District maintenance or local highway maintenance dge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(865) 712-8292		
DISTRICT MAINTENANCE SUPERVISOR	(865) 223-4919		
TENNESSEE HIGHWAY PATROL	(865) 594-5793		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.     </li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspect	ion:		
Latest Bridge Inspection Report Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	pe printed with the following message:		
SAFETY HAZARD KEEP	AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24