HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 73SR0290007

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: S ROANE ST CROSSING: BARNETT BRANCH

LATITUDE:: N 35.94265 DEGREES

COUNTY: ROANE ROUTE: SR029 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 8.84

LON	NGITUDE: W 84.53987 DEGREES	YEAR BUILT: 1968	
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE - STRIN OR GIRDER	GER/MULTI-BEAM APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON S	TEEL PILE FOUNDATION	
BENTS:	CONCRETE COLUMN FOUR OR MO	RE POST BENT ON STEEL PILE FOUNDATION	
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION ————————————————————————————————————	
		our cannot be determined. The bridge shall be monitored for distress in lieu of installing scour countermeasures.	
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
	•	TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
1. C 2. C [] - Chec [] - Chec	Check for plumb of piers or bei k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, ar	n along curb line, both bridge rails and outer edge of bridge deck. nts.	
<u>If Closure is</u>	recommended:		
Coun temp	ity or City Maintenance Person	cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may	
[] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)			
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer	
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked	
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
REGION BRIDGE ENGINEER	(865) 712-8292	
DISTRICT MAINTENANCE SUPERVISOR	(865) 223-4919	
TENNESSEE HIGHWAY PATROL	(865) 594-5793	
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 		
COMMENTS:		
Suggested List of Equipment to conduct the Inspec Latest Bridge Inspection Report Scour POA Report with the above Checklist Bridge Design Plans, if available	tion:	
Tape measure with weight		
Plumb bob		
Range Pole	'an a mintad with the fallowing massage.	
A 1000 Foot Roll of yellow Polyethylene Barricade T		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19