## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 84SR0030015

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: **HWY 51 N**CROSSING: **TOWN CREEK** 

LATITUDE:: N 35.57747 DEGREES
LONGITUDE: W 89.64308 DEGREES

COUNTY: TIPTON
ROUTE: SR003
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 17.60
YEAR BUILT: 1922

		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE
W C. 7	CONCRETE THE BEAM	
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	ENT ON TIMBER PILE FOUNDATION
BENTS:	CONCRETE COLUMN TWO POST B	BENT ON TIMBER PILE FOUNDATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
		our cannot be determined. The bridge shall be monitored for distress e in lieu of installing scour countermeasures.
		- INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert
		[ ] TDOT District or Local Maintenance Personnel
		[ ] THP or Local Law Enforcement Personnel
		[ ] Other:
Things to c	heck on a bridge during flood	<u>s:</u>
[ ] - Span	movement - horizontally as w	rell as vertically
1. 0	Check displacement / deflectio	on along curb line, both bridge rails and outer edge of bridge deck.
2. (	Check for plumb of piers or be	nts.
[ ] - Chec	k for embankment erosion	
[ ] - Chec	k for drift build-up on piers or	bents
[ ] - Chec	k pier exposure, if possible, a	nd compare to previous inspection
[ ] - Revie	ew the latest bridge inspection	report versus current field conditions
K 01		
	s recommended:	
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may.
		Supervisor ( if bridge is State maintained )
	(2) City or County Highwa	ay Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.	

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	tate District maintenance or local highway maintenance bridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspe	ection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:		
SAFETY HAZARD KEE	EP AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19